



# VP920b

19" HEIGHT ADJUSTABLE SLIM BEZEL LCD DISPLAY WITH  
4MS CLEARMOTIV™ HD BROADCAST-QUALITY VIDEO



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	19" color TFT active matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	500:1 (typ)
	Viewing Angles	160° horizontal, 140° vertical @ contrast ratio > 5:1
	Response Time	4ms gray-to-gray (avg); 8ms white-black-white (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	250 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog/Digital	RGB analog (75 ohms, 0.7/1.0 Vp-p)/DVI (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 24~82kHz, F <sub>V</sub> : 50~85Hz
	Sync	H/V separated (TTL), composite sync on green
<b>COMPATIBILITY</b>	PC	VGA up to 1280x1024 non-interlaced
	Mac***	Power Mac™ G3/G4/G5 up to 1280x1024;
<b>CONNECTOR</b>	Analog/Digital	15-pin mini D-sub (1)/ DVI-D (1)
	Power	Internal power adapter, 3-pin (CEE22) plug
<b>AUDIO</b>	Speakers	2x1-watt
<b>POWER</b>	Voltage	AC 100~240V, 50/60Hz (auto switch)
	Consumption	38W (typ)
<b>CONTROLS</b>	Basic	Power, 2, up, down, 1
	OnView®	Auto image adjust, contrast, brightness, input select (analog, digital), audio (volume, mute), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user color - RGB), information (resolution, H.frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>OPERATING CONDITIONS</b>	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical (mm)	416mm x 479mm x 238mm
	Physical (in.)	16.4" x 18.9" x 9.4"
<b>WEIGHT</b>	Net	13.9 lb. (6.3 kg)
	Gross	18.3 lb. (8.3 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B (ICES), CB, CE, ICES-003B, ISO13406-2, TUV/GS, TUV ERGO (covers ISO13406-2 & MPR II), TUV-S, NOM, GOST-R, ENERGY STAR®, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'03 and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight

**ViewSonic®** 

*the choice of professionals*

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Pivot software not included. \*\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12926-00B-03/06] VP920b-1

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)